

PageStream 466 Plus Technical Specifications

| | |
|------------------------|--|
| Printing Method | LED Plus Imaging Electrophotography (two component system) |
| Toner System | Standard: one black developer unit Optional: MICR via Quick Change Developer Station |
| Fusing Method | Heat and Pressure |
| Print Quality | Standard: 240 and 300 dots per inch quality switchable Multiple Resolution Mode |
| Printing Speeds | Letter-sized, portrait, two-across (8.5 x 11 inches) – 466 ipm Letter-sized, landscape, one-across (8.5 x 11 inches) – 302 ipm Invoice, landscape, two-across (6 x 9 inches) – 854 ipm |
| Maximum Printable Area | Pinfed Paper: 17 inches Pinless Paper: 18 inches |



Monthly Capacity Up to 12 million images

Paper Input

Form Sizes Width: 6.5" to 18" infinitely variable
Length: 3" to 28" in 1/6" increments
Length fold to fold: 6" to 14" for stacking purposes

Form Type One part continuous form
Plain white paper stock
Color stock; Card stock,
Recycled content paper
Preprinted, Adhesive labels,
Carbonless, Pressure seal, ID cards
Perforated, Punched, or Drilled

Form Weight 18 - 40 lbs. Bond Basic Weight (17 x 22)
Grammage 70 to 160 g/m² ± 5%
Other weights subject to evaluation

Paper Feed Continuous forms, box, or roll feed

Paper Output

Capacity Forms 6" to 14" can be stacked in Internal Stacker
Maximum stack height: 17.7", equivalent to 3,300 pages at 18 lbs. bond paper
Roll (unlimited)

Post-Print Handling Automated Integrated Power Stacker
Standard Océ Certified Post-Processing devices
(i.e. Automatic Stacker, Folder, Cutter, Job Separator, Rewinder, Color

| | |
|----------------------------|---|
| | Imprinter) |
| Post-Print Attachments | Standard: ADI (Additional Device Interface) Optional: IPPI (Intelligent Post-Processing Interface) for online attachment to various post-processing equipment Océ Verification Manager |
| Controller | |
| Technology | SRA2 (Scaleable Raster Architecture) |
| System Attachments | Standard: Choose one of the following: S/370/390, Channel, ESCON, SCSI, IEEE 1284, TCP/IP (Ethernet) Optional: A second System Attachment |
| Page Description Languages | Standard: Choose two from the following: IPDS, Page Mode, Enhanced Mode, Compatibility Mode Printer Control Language (PCL) 5e Optional: Choose two additional Page Description Languages |
| Options | Xerox DJDE and Metacode, PostScript via Océ PRISMA Print server solutions Océ PRISMA server family Océ Distribution Manager |

Physical

| | |
|--------------------|--|
| Weight | 2,514 lbs. |
| Dimensions | Height: 60.3" Width: 90.0" Depth: 37.0" |
| Power Requirements | Voltage: 208 V, 3-phase, 49 Amps Frequency: 60 Hz, +/-1 Hz Operating: 14.6kVA Standby: 2.4kVA |
| Customer Supplied | Russell Stoll In-line receptacle #7428/78 Or Russell Stoll wall receptacle #7324/78 |
| Océ Supplied | Power cable (4 wire –3 phase + ground) and Russell Stoll plugs #7328/78 |

Environmental

| | |
|-------------------------------------|---|
| Optimum Operating Temperature Range | 59° - 80°F |
| Optimum Operating Humidity Range | 45% – 55% |
| Acoustic Noise | Operating: 67 db Standby: 61 db |
| Heat Dissipation | Operating: 42,990 BTU / hr Standby: 7,170 BTU / hr |
| Approved Standards | UL, FCC Class A |