







# **Transpromotional**

### **Roll to Stack Solution with Dynamic** Perforation/Punch and Web Merger

The DP8 dynamic perforation module is the first solution that combines perforation in the vertical and cross directions along with punching – all in one unit. "Dynamic" means the ability to change the punching, perforating or hole pattern from sheet to sheet. It is particularly interesting for transpromotional applications or personalized mailers. Coupons, payment slips and other elements can be integrated into practically any type of document, even those with forms that vary with each sheet.

#### Technical Data\* | Roll to Stack with DP8 - WM6 - LS6-28

Max. roll diameter:	54"	1370 mm
Web width:	13" – 20.5"	330 – 520 mm
Production speed:	up to 433 ft/min	up to 130 m/min
Paper weights:	60 – 120 gsm	16 – 32 lb bond
Stack height:	4" - 10"	100 – 250 mm
Variable chip-out:	1/4" - 1"	6 – 26 mm
Format length:	5.5" – 28"	140 – 711 mm
File hole punching:	2-, 3-, 4 hole pattern Ø 5,5 – 8 mm	

Unwinder **Dynamic Perforator/Puncher DP8** 

Options: Stacker LS6, Offset separator SE6, Gutter cut, Transfer Station TS6













Full bleed products with CS6-II


Quality control with W16

Web merging with WM6


## Roll to Stack Solution with Dynamic Perforation/Punch

Dynamic perforation and punching combined in a modular concept. In 2-up production individual processing of the two web halves is possible. Combined use of three different is possible in a single module (dynamic perforation in the vertical and cross direction, and dynamic file hole punching).


Technical Data*	Roll to Stack	with DP8	
Max. roll diameter:	54"	1370 mm	
Web width:	6.5" – 20.5"	165 – 520 mm	
Production speed:	up to 500 ft/min	up to 150 m/min	
Paper weights:	60 – 160 gsm	16 – 40 lb bond	
Stack height:	9 7/8"	250 mm	
Variable chip-out:	<sup>3</sup> / <sub>16</sub> " – 2 <sup>3</sup> / <sub>4</sub> "	4.8 – 70 mm	
Format length:	5.5" - 19"	140 – 482 mm	
File hole punching:	2-, 3-, 4 hole patte	rn Ø 5,5 – 8 mm	
Options: Large sheet	delivery LS6-28", Dyi	na-Cut	



#### Dynamic Perforation and Punching module DP8 - Five different configuration possibilities









PerfEditor: easy job setup



Perforating and Punching



Efficient 2-up production