

# Vertical Stack Turner

## Easily turn fanfold stacks 180°



- ✓ *Enable inserter feeding both A-Z and Z-A*
- ✓ *Flexible off-line operation*
- ✓ *Stackable trolleys, minimizing space requirements*
- ✓ *Easy to use balanced rotation*

The Vertical Stack Turner flips over a trolley cart loaded by the Tecnau Folders, enabling users who print transactional applications A to Z to reverse the output stack and feed their inserters in A to Z sequence, or similarly allowing Z to A print to insert Z to A as well.

The Folder module of the Fanfold system builds printed stacks up to 39 inches (991 mm) high and outputs each stack on a trolley. Trolleys are wheeled over and docked into the off-line Stack Turner. A second, empty trolley is in an upside-down position at the top of the Vertical Stack Turner. The operator pushes a button to firmly compress the printed stack between the two trolleys. The stack is then easily pivoted 180° with a small push from the operator (see bottom photo at left for a stack in mid-turn).

With the Vertical Stack Turner, users can take full advantage of a flexible, mixed-vendor mailroom, by providing stacks in whichever orientation is required, regardless of printer sequencing.

### Technical Specifications

#### Performance / Media

Web width	8" - 21"	200 - 530 mm
Form length	8" - 17"	200 - 430 mm
Stack height	7" - 39"	180 - 990 mm

#### Electrical

Power	2.5A, 200 - 240 VAC, 50/60 Hz or (North America) 5A, 110 - 120 VAC, 50/60Hz	
Consumption	610 W (in use)	25 W (idle)
Heat output	105 kcal/h - 439 kJ/h - 417 BTU/h	

#### Environmental

Temperature	50 - 90° F	10 - 32° C
Acoustics	90 dB(A) max.	
Humidity	50 +10%	


#### Dimensions

Length	41"	1040 mm
Width (inc. display)	60"	1525 mm
Height	61"	1550 mm
Weight	845 lb	385 kg
Color	Gray	

#### Approvals

CE(98/37/EC), EMC(2004/108/EC),  
LVD (2006/95/EC), UL, cULus,  
FCC 47 CFR Part 15, Sub Part B, Class A

### Service Area



## Product Specifications



16022015

©2015 Tecnau. All rights reserved. The Tecnau name and logo are trademarks of Tecnau. Tecnau reserves the right to make any technical amendments without prior notification.



**TECNAU**  
w w w . t e c n a u . c o m

Europe	Italy	+39 0125 631678	info.it@tecnau.com
	Sweden	+46 372 256 00	info.se@tecnau.com
Americas	USA	+1 978 608 0500	info.us@tecnau.com
Asia Pacific	China	+86 159 00710147	info.cn@tecnau.com
	Singapore	+65 6793 9478	info.sg@tecnau.com